

CARACTERISTIQUES

| | |
|-------------------|--------------|
| Référence : | 1543313 |
| Color : | Transparent |
| Lenght (mm) : | 128 |
| Material : | Plastique ps |
| Pack par carton : | 5,41 |



USE

| | |
|--------------------|-------|
| Traditional Oven : | Non |
| Microwave : | Non |
| Freezer : | Non |
| Reheating : | Non |
| T° mini : | -18°C |
| T° maxi : | 80°C |

PACKAGING AND LOGISTICS

| | |
|-------------|-----|
| Packaging : | 250 |
|-------------|-----|

PACKAGE FEATURES

| | |
|--------------------|---------------|
| Unités par pack : | 25 |
| Colis poids brut : | 1 kg |
| Largeur carton : | 16 |
| Longueur carton : | 27 |
| Hauteur carton : | 10,5 |
| Pack par carton : | 10 |
| Colis code barre : | 3700466014272 |

PALLET FEATURES

| | |
|-----------------------------|------|
| Cartons par couche : | 13 |
| Couches par palette : | 7 |
| Total cartons par palette : | 91 |
| Largeur palette : | 80 |
| Longueur palette : | 120 |
| Hauteur palette : | 93,5 |

Compliance with current European regulations: materials in contact with foodstuffs.

Compliance is subject to conditions of storage, handling and use taking into account the respect of the characteristics of the material and the packaging referred to above. All information is given in good faith and for guidance only. It does not constitute a recommendation to use the product. It is the responsibility of the buyer to verify that the product is suitable for the intended use. All modifications or changes in operating conditions must be brought to our attention. All our products comply with the regulations concerning materials intended to come into contact with foodstuffs, as well as the regulations aimed at reducing packaging at a minimum.

A certificate of compliance is available on request.

Data sheet downloaded from www.firplast.com. Firplast. All rights reserved. FIRPLAST - 4, rue de Provence - 69800 SAINT-PRIEST - Tel. 04 72 23 66 66 - Fax. 04 78 20 54 40 - contact@firplast.com S.A.S. au Capital de 600 000€ - RCS LYON 327 963 021 - APE 4669C